

C&W SINGLE SLUMP MASTER G3

Easy access to truck's chute for adding fiber additives, checking slump or washing trucks

OSHA-approved handrails and stairway

Optional Pallet Rack, can be mounted at mid-level or high-level (shown at mid-level). Rated for a max of 500 pds.

Counter-balance Mechanism to automatically raise and lower the Pivot Deck with hands-free operation. Rated at 500 pds.

Slump Master **must** be anchored to at least a 6" concrete slab. 8" anchor bolts are provided.



Folding Handrails

Single Slump Master in up-right position, waiting to be engaged.

The entire Slump Master is galvanized, except for fiberglass decking and stairs.

A Single Slump Master is shown, to upgrade to a Double, a pivot deck is added to the other side of the tower. No additional tower needed, like the previous model.



**Put
Safety
First!**

C&W SINGLE SLUMP MASTER G3



Meniscus Fiberglass Decking that provides self-cleaning



Sand-Infused Fiberglass stairs that provides self-cleaning

Single or Double Slump Master ready to ship, can ship LTL motor freight or a flatbed.



Shipping Dimensions:

Single: 3'H, 4'W, 8.5'L

Double: 5'H, 4'W, 8.5'L

If optional Wash-down platform is purchased, dimensions will change.